



参数表 Parameter Table

型号 Model	SCR-25AR	SCR-25BR
测量轴数 Measuring axis number	单轴 Single Axis	双轴 Double Axis
测量范围 Measuring range	0.1mm-25mm、1/256"-63/64"	0.1mm-25mm、1/256"-63/64"
测量精度 Measuring accuracy	±0.002mm	±0.002mm
测径仪扫描速度 Scanning speed of diameter gauge	600-1000次/秒 600-1000 times/second	
分辨率 Resolution	0.001mm	
通讯接口 Communication interface	RS485 (support Modbus RTU)	
仪器尺寸 Instrument size(mm)	290*66*170	320*60*280
重量 Weight	5KG	6.5KG

参数表 Parameter Table

型号 Model	SCR-25BYB
测量范围 Measuring range	0.1mm-25mm、1/256"-63/64"
测量精度 Measuring accuracy	±0.002mm
MES系统数据接口、RS485接口、以太网接口 Data interface of MES system, RS485 interface, Ethernet interface	
测量数据实时显示/记录存储 Real-time display and recording storage of measurement data	
记录历史报警数据、报警位置、报警值大小 Record historical alarm data, alarm position, alarm value size	
记录历史测量过程曲线、任意查询 Record historical measurement process curves, and arbitrary query	
数据处理功能:最大值、最小值、平均值 Data processing functions: maximum value, minimum value, average value	
U盘存储和打印支持 USB storage and printing support	
测试软件,PLC,人机触摸显示屏 Test software, PLC, human-machine touch display screen	
控制系统刹车 Brake control system	
摇摆速度和高度可调 Swing speed and height adjustable	
旋转测量头装置 Rotating measurement head device	

